

## Declaration of Performance

In accordance with Regulation (EU) No 305/2011, as amended by the UK Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and 2020

**1. Unique product-type reference:**

Magply Magnesium Oxysulphate Board.

**2. Type:**

Self-supporting composite lightweight panels of 3, 6, 9, 12, 18 & 20mm thickness.

**3. Intended use:**

For use in external walls, claddings, internal walls, ceilings, flooring, roofing, pattering, facades, modular construction, and recovery board applications.

**4. Manufacturer:**

Name: IPP Limited

Address: Bradwell Hall,  
Essex, CM0 7HX

**5. Authorised Representative:** N/A

**6. System or systems of AVCP:** System 3

**7. In case of the declaration of performance concerning a construction product covered by a designated standard:**

British Board of Agrément, UK Approved body number 0836.

Issued UKTA-0836-23/6858

**8. N/A**

**9. Declared Performance**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	Euroclass A1 (Non-combustible)	BS EN13501-1: 2018
Thermal conductivity	0.495 W/mK	BS EN 12667: 2001
Pull-through strength (Axial loading test with drywall screws)	1195N (9mm), 1415N (12mm)	ETAG 006:2000 / Amended: 2012
Racking strength	5.08 kN/m (9mm)	BS EN 1995-1-1: 2004
Resistance to moisture	Category B	BS EN 12467: 2012
Dimensional tolerance	Level 1	BS EN 12467: 2012
Resistance to mould	Resistant	BS 3900-G6: 1989
Impact resistance — soft body	9mm — Category I & II	EOTA TR001: 2003, §2
Impact resistance — hard body	9 & 12mm — Category I & II	EOTA TR001: 2003, §3

**10. The performance of the product identified above is in conformity with the declared performance identified in the table.**

This declaration of performance is issued under the sole responsibility of the manufacturer as identified above.

**Signed for and on behalf of the manufacturer by:**

G.M. Pirret, Director

**Signature:**



**Place and date of issue:**

Essex, UK — 01/04/2025