

1. Product Name

Product name	Magply FR Intumescent Acrylic Sealant		
Use	A water-borne acrylic sealant with fire and smoke resisting capability for internal gap sealing.		
Supplier	IPP Ltd Bradwell Hall Bradwell on Sea Essex CM0 7HX United Kingdom	Tel: 0044 (0)1621 776252 Fax: 0044 (0)1621 776688 Email: sales@magply.co.uk Emergency Tel: +44 (0) 1621 776252 (office hours only)	

2. Hazards Identification

Regulation EC 1272/2008	This product is not classified as hazardous according to regulation (EC) 1272/2008 (CLP)		
Label elements	<ul style="list-style-type: none">• Regulation EC 1272/2008• Signal word: None• Hazard statement: None• Other hazards: None		

3. Composition

Ingredient	CAS No.	EC No.	REACH registration No.	Classification According to Reg. (EC) 1278/2008 (CLP)	% W/W
Dipropylene Glycol Dibenzoate	27138-31-4	248-258-5	01-2119529241-49-0002	H412 Aq Chron – 3	2-5%

4. First Aid Measures

General

In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

- Skin Contact: Wash skin thoroughly with soap and water or a recognised skin cleaner. DO NOT use solvents or thinners.
- Eye Contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes holding eyelids apart, and seek medical advice.
- Ingestion: If accidentally swallowed wash mouth with water and give water to drink. DO NOT Induce vomiting.
- Inhalation: Remove to fresh air.

Symptoms and Effects

- Skin contact: No symptoms anticipated
- Eye contact: There may be irritation and redness
- Ingestion: No symptoms anticipated. If there is any persistence of discomfort seek medical advice
- Inhalation: No symptoms

5. Firefighting Measures

The liquid product is 'non-flammable'.

Extinguishing Media

Recommended: alcohol resistant foam, CO², powder, water spray/mist.

Special Hazards

As the products contain combustible organic components, fire will produce hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health.

Advice for firefighters

Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run off from fire fighting to enter drains or water courses.

6. Accidental Release Measures

Personal precautions and protective equipment: Refer to section 8 of SDS for details

Environmental precautions

Do not allow to enter drains or water courses. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes, the relevant Environment Agency.

Containment and clean up

Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth, and place in a suitable container for disposal in accordance with the waste regulations (see section 13).

7. Handling and Storage

Precautions for safe handling

Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8.

The Manual Handling Operations Regulations may apply to the handling of containers/packages of this product. 25 cartridge pack size = 7.75L. 12 cartridge pack size = 3.72L. Cartridge pack weight = Literture x Specific Gravity (Specific Gravity can be found in section 9)

Precautions for safe storage

Keep containers closed when not in use. Never use high pressure to empty. The container is not a pressure vessel. Ensure good housekeeping and regular safe removal of waste materials. Observe label precautions - Store between 5°C and 25°C in a dry well-ventilated place away from sources of heat. Protect from frost. Keep out of reach of children. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

8. Exposure & Personal Protection

Engineering Measures: Provide adequate ventilation during application and drying. Where practicable this should be achieved by the use of local exhaust ventilation. If this is not sufficient to maintain concentration of solvent vapours below the relevant Occupational Exposure Limit, suitable respiratory protection must be worn (see 'Occupational Exposure Controls' below).

Exposure Limits

Substance

Occupational Exposure Limits

8 hr LTEL (1) 15 min STEL(2) - ppm mgm-3 ppm mgm-3

Notations

- (1) Long-term exposure limit - 8 hour time weighted average.
- (2) Short-term exposure limit - 15 mins time weighted average.
- (R) Recommended by suppliers
- (A) Allocated limits by analogy with similar materials
- (SK) Risk of absorption through unbroken skin
- (Sen) Capable of causing sensitisation by inhalation

Occupational Exposure Controls

All Personal Protective Equipment (ppe), including Respiratory Protective Equipment (rpe), used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

Respiratory Protection

If exposure to hazardous substances identified in section 8 cannot be controlled by the provision of natural ventilation e.g. work in enclosed areas, exposure should be controlled, where reasonably practicable, by the use of mechanical exhaust ventilation; when this is not reasonably practicable, suitable respiratory protective equipment must be worn.

Hand Protection

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

Eye Protection

Eye protection designed to protect against liquid splashes should be worn.

Skin Protection

Cotton or cotton/synthetic overalls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a recognised skin cleaner. **Always wash your hands before eating, smoking or using the toilet.**

9. Physical and Chemical Properties

Physical Properties	Chemical Properties
Physical state	Viscous paste
Flash point	>100°C
Viscosity	N/A
Specific Gravity	1.60-1.68 @ 20 °C
Solubility in water	miscible when wet.
pH	7.7-9.0
TVOC	0.005 mg/m ³

10. Stability and Reactivity

Reactivity

No data available

Chemical stability

Stable under normal temperature and storage conditions

Possibility of hazardous reactions

None known

Conditions to avoid

See section 10.3

Incompatible materials

See section 10.3

Hazardous decomposition products

Oxides of carbon released under high temperature (>300°C)

11. Toxicological Information

Information on Toxicological effects

There is no evidence of toxicological effects of the product

Ingestion: May cause discomfort if swallowed. May cause stomach pain

Skin contact: May be Irritating to skin

Eye contact: Risk of irritation to eyes.

Sensitisation: Not sensitising

STOT: Not classified

12. Ecological Information

Ecotoxicity not regarded as dangerous for the environment

Not considered toxic to fish

Persistence and degradeability

The product is not biodegradeable.

Bio accumulative potential

The product is not bio accumulating

Mobility in soil

Not mobile

Results of PBT and vPvB assessment

Not classified as PBT/vPvB

Other adverse effects

None known

13. Disposal Considerations

Do not allow to enter drains or water courses. Wastes, including emptied containers, are controlled waste and should be disposed of in accordance with regulations made under the 'Control of Pollution Act' and the 'Environmental Protection Act'. Using information provided in this data sheet, advice should be obtained from the relevant Environment Agency whether the Special Waste Regulations apply.

14. Transport Information

Transport within the users premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Onwards transport subsequent to purchase: Transport to be in accordance with ADR for road, IMDG for sea and ICAO/IATA for air.

Proper shipping name: The product is not classified as dangerous for carriage.

UN number:

Hazard class:

Packing group:

Sub-hazard class:

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Control of Substances Hazardous to Health Regulations 2002
 Environment Act 1995
 Management of Health and Safety at Work Regulations 1999
 Personal Protective Equipment at Work Regulations 1992
 Special Waste Regulations 1996 as amended

Health and Safety Executive Guidance Notes

HS(G)258	Controlling Airborne Contaminants at Work
EH40	Occupational Exposure Limits
EH44	Dust: General Principles of Protection
HS(G)53	The Selection, Use and Maintenance of Respiratory Protective Equipment
HS(G)71	Storage of Packaged Dangerous Substances
L23	Manual Handling Guidance on Regulations

British Standards Publications

EN420: General Requirements for Gloves
EN166: Personal Eye Protection: Specifications

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of EU Regulation 1272/2008 (CLP). The product should not be used for purposes other than those identified without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular application.